



- NOTE: 1) HYDRO @ 325 PSIG. MIN.
 2) ALL NPT ARE SA-182-304 S.S.
 3) UHA-51 (e)(2) NO IMPACT TESTING.

SHELL / HEADS		16-VC-30-L	
.135" SA-240-304 S.S. 2:1 S.E.		REV. 3-22-11	
JOGGLE - .129 OFFSET		DATE: 12-12-06	
.187" SA-240-304 S.S.		FOR: HANSON STANDARD	
		VERT. AIR TANK	
		SURFACE AREA = 14.8 SQ. FT.	
		INSIDE: UNPAINTED - PASSIVATE	
M.A.W.P. 250 PSIG. @ 200 °F		OUTSIDE: BEAD BLAST & PASSIVATE	
M.D.M.T. -155 °F @ 250 PSIG.		CAD-"B" SIZED UNDER "STD"-SERIES	
ASME SECTION VIII DIV. 1, 2010 ADD 2010		BY: J.G. SCALE: 1"=12"	
X-RAY: RT-NO		ROY E. HANSON JR. MFG.	
GALLONS: 30 WT. 131 LBS.		1600 E. WASHINGTON BLVD.	
SERIAL NO.		LOS ANGELES, CA 90021	
N.B. NO.			